

GENERAL SPECIFICATIONS

Sampling Rate	96 kHz
A/D, D/A Convert	24 bits
Headroom	19dB
Cross Talk (Line)	88dB
Frequency Response	20Hz ~ 20kHz
Total Harmonic Distortion	0.005% or less
Signal-to-Noise Ratio	105dB(LINE) (at full scale) 88dB (PHONO) (at full scale) 84dB(MIC) (at full scale)
Power Source	AC 100V (50/60Hz)
Electricity	54W
Dimensions	428(W) x 359.3(D) x 187.5(H) mm 19 (W) x 14-2/16 (D) x 7-3/8 (H) 19', 6 unit for the mixer, 1 unit for connectors.
Net Weight	12.1 kg 26 lb 11 oz

Input Specs & Terminals

Digital	4 x (RCA) / Coaxial 2 x Mini Digital Link Connectors (AUDIO)
CD / Line	6 x (RCA) and 4 x (Phone Jack 6.3 mm) 12dBu / 22k
Phono	6 x (RCA) -52dBu / 47k
Mic / Sub Mic	1 x(Combi Phone/XLR) & 2x(Phone Jack 6.3) -52dBu / 3k
Return	2 x (Phone Jack 6.3mm) -12dBu / 22k

Output Specs & Terminals

Master Out 1	1 x (XLR) +2 dBu / 600 Ohm
Master Out 2	1 x (RCA) +2 dBu / 10k
Booth	1 x (Phone Jack 6.3mm) +2dBu / 600 Ohm
Record	1 x (RCA) -8dBu / 10k
Send	2 x (RCA) -12 dBu / 10k
Midi Out	1 x (5 pin DIN)
Headphone Monitor Out	1 x (Phone Jack 6.3mm) +8.5 dBu / 32 Ohm