

DRM-1004 Specifications:

Disc Capacity: Up to 100 DVD-ROM, DVD-R or CD-ROM discs

Configurations: Up to four 2.5X DVD-ROM read drives

Disc Swap Time: Less than six seconds

Disc Load Time: Less than three seconds

Sustained Data Transfer Rate: 2.7 Mbytes/second (2.5X DVD-ROM); 3.0 Mbytes/second (20x CD-ROM)

Random Average Seek Time: Less than 120 ms (DVD-ROM); Less than 80 ms (CD-ROM)

Random Average Access Time: Less than 150 (DVD-ROM); Less than 90 ms (CD-ROM)

Disc Spin Up Time: Max 3 seconds

Disc Spin Down Time: SCSI-2 (SCSI IDs can be individually set for each drive and for the changer robotics).

Reader Interfaces: SCSI-2 (SCSI IDs can be individually set for each drive and for the changer robotics).

Changer Interface: SCSI-2 (single-ended)

Platform Support: DOS, Windows 95, Windows 3.1 and Windows NT, Macintosh, OS/2, Novell, UNIX, HP, DEC ODF/Alpha, Sun OS and Solaris.

Software Drivers: Software support available from third-party vendors.

Dimensions

(W x H x D): 10.5" x 19"x 23"

Mean Swaps Between Failure: 1,000,000 Swaps