

# CAC-V3200 Specifications

General	
Type	CD Autochanger
Audio Channel	2 channels
Discs	Standard 4-3/4 inch (12cm) Compact Disc
Quantization	16 bit linear
Sampling frequency	44.1kHz
D/A converters	1 bit DAC
Digital attenuator	0 to -84dB, -∞dB
Speed Control	±10%, 1% step
Number of players	2 players
Disc change time	30 sec. or less
Access time	6 sec. or less
Capacity	300 discs
Power supply	AC 120V, 60Hz
Power consumption	60W
Dimensions (W × D × H)	14-3/16 × 14-3/16 × 23-1/4 inch (360 × 360 × 590mm)
Net weight	62.7 lbs (28.5kg)
Audio Data	
Analog Output	
Output level (1kHz, 100%)	2.2V ±0.5Vrms (Type RCA × 3) 4dBm rms, +1.8dB, -2.2dB (Type XLR 3 × 2)
Output impedance	1k ohms or less
Signal to noise ratio	CDP1, CDP2 110dB (RCA, XLR) MIX 105dB (RCA)
Frequency response	±0.5dB at 20Hz to 20kHz
Distortion	0.007% at 1kHz (EIAJ)
Channel separation	CDP1, CDP2 103dB (RCA, XLR) MIX 97dB (RCA)
Residual noise	100µVrms or less
Level difference (L/R)	1.5dB or less
Digital Output	
Output level	0.5V ±20% (P/P) (EIAJ) (Type RCA × 2)
Output impedance	75 ohms ±20% (EIAJ)
Rise times	70 ns or less (EIAJ)

## Dimensions

Unit: Inch (mm)

