

DRM-600X Specifications

Supported Disc Formats	CD-ROM, CD-DA
Media Diameter	120 mm
Media Handling	6 Disc Magazine
Number of Discs	6 Discs
Disc Change Time	Less than 7 seconds
Interface	SCSI
Data Transfer Rate (Sustained)	153 KB/s (1X)
Data Transfer Rate (Burst)	1.5 MB/s
Random Average Access Time	600 ms
Data Buffer Capacity	64 KB
Data Block Size	2048 Bytes
Disc Startup Time	max. 3 seconds
Disc Spin Down Time	max. 2 seconds
Mean Time Between Failure	20000 Power On Hours
Headphone Connector	Stereo Mini-Jack
Output Level	1.8 ± 0.5 Vrms (Line Out)
Frequency Response	4 ~ 20000 Hz (±2 dB)
Total Harmonic Distortion	0.1% or less
Dimensions (W x H x D)	210 x 115 x 408 mm
Operating Voltage	120V DRM-600, 240V DRM-610, 120/240V DRM-600A
Net Weight	5.3 kg
Operating Temperature	5°C to 40°C
Operating Humidity (non-condensing)	5 to 85% RH
Storage Temperature	-20°C to 60°C
Storage Humidity (non-condensing)	5 to 85% RH