

DRM-602X Specifications

Supported Disc Formats	CD-ROM, CD-R, CD-DA, CD-ROM XA
Media Diameter	120 mm
Media Handling	6 Disc Magazine
Number of Discs	6 Discs
Disc Change Time	Less than 5 seconds
Interface	SCSI-2
Data Transfer Rate (Sustained)	307 KB/s (2X)
Data Transfer Rate (Burst)	4 MB/s
Random Average Access Time	300 ms
Data Buffer Capacity	256 KB
Data Block Size	2048 Bytes / 512 Bytes
Disc Startup Time	max. 3 seconds
Disc Spin Down Time	max. 2 seconds
Mean Time Between Failure	20000 Power On Hours
Headphone Connector	Stereo Mini-Jack
Output Level	1.7 ± 0.5 Vrms (Line Out)
Frequency Response	4 ~ 20000 Hz (±2 dB)
Total Harmonic Distortion	0.1% or less
Dimensions (W x H x D)	210 x 104.7 x 370.5 mm
Operating Voltage	AC 120/240 V
Net Weight	4.1 kg
Operating Temperature	5°C to 40°C
Operating Humidity (non-condensing)	5 to 85% RH
Storage Temperature	-30°C to 60°C
Storage Humidity (non-condensing)	5 to 90% RH