


DRM-604X SPECIFICATIONS

Media Type	CD-ROM, CD-Audio XA Mode 2, Form 1 and 2
Media Diameter	120mm
Interface	SCSI, SCSI-2
Block Size	2048/512 Byte (selectable)
Data Transfer Rate	614/1534 Kilobytes/Sec 4.2 MBytes/Sec (Burst)
Access Time	300 mSec
Disc Change Time (without Spin-up, Spin-down)	less than 5 Sec
MTBF	20,000 hr
Regulatory Approvals	UL, CSA, FCC Class B VDE, TÜV, SEMKO BEAB, NEMKO, DEMKO FMKO, SEV
Audio Performance	
Frequency Response	4 – 20,000Hz \pm 2dB
Total Harmonic Distortion	0.1% (Max)
Output Voltage	1.7V r.m.s. (line out) \pm 0.5V (10K Ω)
Physical Characteristics	
Dimension (W x H x D)	210 x 104.7 x 370.5mm
Weight (Net)	4.1kg
Weight (Shipping)	6.0kg
Operating Voltage	100 – 240V 50/60Hz
Rated Current Consumption	AC 120V 0.4A AC 240V 0.2A
Max. Current Consumption	AC 120V 0.5A AC 240V 0.25A
Environmental Conditions	
Operating Temp	5 – 40°C
Storage Temp	-20 – 60°C
Humidity (non-condensing)	5 – 85%/RH
Accessories	
DRM-A600	6 Disc Magazine
PCA-02	SCSI Daisy Chain Cable


Included with Drive

DRM-A600
Software (IBM PC/AT/XT and Macintosh)
Operation Manual
Audio Cable
Power Cable

Dimensions



Configuration & Functions



*For details, contact address given below.

- Design and specifications subject to change without notice.
- LaserMemory is a trademark of Pioneer Electronic Corporation.
- Photo CD symbol is a trademark of Kodak used under license.
- All other product names are trademarks of their respective companies.

