

S-VSL3

2-WAY FRONT TALL SPEAKER SYSTEM



- New High-Quality Speakers with Slim, Contemporary Design
- 3-1/4-inch (8.3cm) Cone Woofer (x2) for Dynamic Sound Reproduction
- Acoustic Balance Drive (ABD) Technology Dampens Standing Waves for Clearer Bass
- 3/4-inch (2cm) High-Efficiency Soft Dome Tweeter
- Wide Frequency Response: 50Hz — 40,000Hz
- Magnetically Shielded for Video Use

S-LF3-CR

3-PIECE ULTRA-THIN SPEAKER SYSTEM



- Compact Center Speaker and Satellite Rear Speakers (L/R)*
- 3-7/16-inch (8.7cm) Flat Woofer (x2) and 3/4-inch (2cm) Tweeter
- Stylish, Ultra-thin, Aluminum-Finish Design
- Speaker Grills Available in Black or White
- 130W Maximum Power for Satellite Speakers
- Frequency Range: 60 — 40,000Hz (Center)/ 65 — 40,000Hz (Rear)
- Magnetically Shielded for Video Use
- Can be Integrated as Part of 5-piece System with S-LF3-F Speakers, with Versatile Mounting Options

* Table-top stands included

S-VSL6C

2-WAY BOOKSHELF SATELLITE SPEAKER SYSTEM



- Designed to Match Pioneer PureVision™ Plasma Displays
- Can be Positioned Vertically, Horizontally or Hung on the Wall* for Versatile Layout
- Stylish Aluminum Extrusion Enclosure
- 3-1/4-inch (8.3cm) Cone Woofer (x2) for Dynamic Sound Reproduction
- 3/4-inch (2cm) High-Efficiency Soft Dome Tweeter
- Magnetically Shielded for Video Use

* Mounting hardware included

S-LF3-F

2-PIECE ULTRA-THIN SPEAKER SYSTEM



- Compact Satellite Front Speakers (L/R)*
- 3-7/16-inch (8.7cm) Flat Woofer (x2) and 3/4-inch (2cm) Tweeter
- Stylish, Ultra-thin, Aluminum-Finish Design
- Speaker Grills Available in Black or White
- 130W Maximum Power for Satellite Speakers
- Frequency Range: 65 — 40,000Hz
- Magnetically Shielded for Video Use
- Can be Used with S-LF3-CR Speakers in an Integrated System of 5 Speakers, with Versatile Mounting Options

* Table-top stands included