

ELITE

A-20

DIRECT ENERGY DESIGN INTEGRATED AMPLIFIER WITH SYMMETRICAL CONSTRUCTION, ALUMINUM PANEL, AND PHONO MM



DESIGN AND BUILD

- › Direct Energy Design Amp
- › Symmetrical Power Amp
- › Clean Ground Construction
- › Isolated Power Supply
- › Source Direct Mode
- › Trans-Stabilizer
- › Speaker A, B, A+B Selector
- › Aluminum Panels
- › Auto Power Down

CONNECTIONS

- › Analog Audio Input (PHONO (MM), TUNER, SACD/CD, AUX, NETWORK, RECORDER)
- › Audio Output (RECORDER, HEADPHONES)
- › SR In/Out
- › AC Inlet

SPECIFICATIONS

- › 50 W + 50 W (20 Hz-20 kHz, 0.1 % THD, 4 ohms)
- › 30 W + 30 W (20 Hz-20 kHz, THD 0.05 %, 8 ohms)
- › THD: 0.01 % (Rated Output -3 dB, 8 ohms, 1 kHz)
- › Guaranteed Speaker Impedance (2 Speaker Terminals): 4-16 ohms (A or B), 8-32 ohms (A+B), 4-16 ohms (Bi-Wiring)
- › Frequency Response: 5 Hz-100 kHz, 0 dB/-3 dB, 20 Hz-20 kHz, ± 0.5 dB (RIAA Equalization) MM
- › Power Requirements: AC 120 V 60 Hz
- › Power Consumption: 135 W
- › Power Consumption During Standby: 0.3 W
- › Dimensions (W x H x D): 17.12 x 5.03 x 14.17 Inches
- › Weight: 15.87 lbs.
- › UPC: 884938160513

Specifications and design subject to modification without notice.
PIONEER, ELITE, and the Pioneer and Elite logos are registered trademarks of Pioneer Corporation.
"SACD" and "Super Audio CD" are trademarks of Sony Corporation